



## SPEC DATA SHEET # OX-QFA-VIVID

4700 Clairton Blvd., Pittsburgh, PA 15236  
Tel: (412) 884-3000 • Fax: (412) 884-3300  
www.oeler.com • sales@oeler.com

# OX-QFA-VIVID

## QUILTED FIBERGLASS ABSORBER

Oeler Industries, Inc. Quilted Fiberglass Absorbers reduce the reflection of sound waves by adding soft, porous, open-celled materials to an environment. The OX-QFA-VIVID product consists of a quilted fiberglass absorber with vinyl facing on both sides. Wall panels are constructed with all edges bound and grommets across the top. Rolls are available 4' wide x 25' long and can be supplied with edges bound or unbound.

### APPLICATIONS:

Typically used when you are trying to reduce the reflection of sound waves or reverberant noise energy within a piece of equipment, a room, or a building.



### FEATURES:

- Class A (or 1) Flammability Rated per ASTM E84
- NRC rating 0.85
- Available colors: gray, white, black, or tan
- Available in either a diamond stitch or straight stitch pattern





Intelligent Acoustic Solutions

**SPEC DATA SHEET # OX-QFA-VIVID**



**DESCRIPTION:**

- Vinyl coated fiberglass cloth facing / fiberglass batt/ non-porous scrim facing

**THICKNESS:**

- 2.0 thick

**STANDARD WIDTH:**

- 48" wide

**ROLL LENGTH:**

- 25' long

**DENSITY:**

- 1.6 lb/ft<sup>3</sup>

**FLAMMABILITY:**

Class A Fire Rated

- Flame Spread: 17.66
- Smoke Density: 22.75

**TEMPERATURE RANGE:**

- -20° to +180° F

**ACOUSTICAL PERFORMANCE:**

**Sound Absorption Data**

Product	Octave Band Frequencies(Hz)						NRC
	125	250	500	1000	2000	4000	
OX-QFA-VIVID	.19	.99	.96	.80	.57	.33	.85

Per ASTM C 423

**SPECIFICATIONS:**

Specifications can be downloaded from our website <https://www.oeler.com/resources/datasheets/> or call us at (412) 884-3000.