



Intelligent Acoustic Solutions

OXC-400

ACOUSTICAL CEILING TILES

Oelex Acoustical Ceiling Tiles are offered as both a sound absorbing as well as a combination sound absorbing/sound blocking tile.

OXC-400 Ceiling Tiles have a black matte facing attached to a 1" or 2" thick rigid fiberglass board and have excellent sound absorption (NRC) ratings.

OXC-400B Ceiling Tiles take the standard OXC-400 tile and add a 1# foil backed mass-loaded vinyl to the backside of the tile for high sound absorption (NRC) and high sound blocking (STC) requirements.



FEATURES:

- Black matte facing
- Custom sizes available
- Excellent acoustical values
- Offered with a vinyl noise barrier for high STC requirements

SPEC DATA SHEET # OXC-400

4700 Clairton Blvd., Pittsburgh, PA 15236

Tel: (412) 884-3000 • Fax: (412) 884-3300

www.oeler.com • sales@oeler.com





Intelligent Acoustic Solutions

SPEC DATA SHEET # OXC-400



WEIGHTS:

OXC-400 — 0.75 lbs./ft²

OXC-400B — 1.75 lbs./ft²

SIZING:

23-3/4" x 23-3/4" or 23-3/4" x 47-3/4" to fit into a standard 15/16" ceiling grid

SPECIFICATIONS:

Specifications can be downloaded from our website <https://www.oeler.com/resources/datasheets> or call us at (412) 884-3000.

FINISH:

Black matte facing

ACOUSTICAL DATA:

NRC Rating

- 1" Thick — 0.85
- 2" Thick — 1.15

STC Rating

- OXC-400B — 26

SUBSTRATE:

6-7# PCF rigid fiberglass core

*OXC-400B adds a vinyl noise barrier

EDGE DETAIL:

Square

MOUNTING OPTIONS:

Grid supplied by others