



SPEC DATA SHEET # GWC\_EX-R

4700 Clairton Blvd., Pittsburgh, PA 15236  
Tel: (412) 884-3000 • Fax: (412) 884-3300  
www.oeler.com • sales@oeler.com

## GWC-EX-R SOUND CURTAINS

The Oelex by Oeler Industries, Inc. GWC\_EX-R is a noise barrier for outdoor applications. This barrier-wall product consists of an exterior grade, UV resistant heavy-duty, one-pound per sq. ft. reinforced loaded vinyl noise barrier. Its high strength polyester fabric reinforcement is utilized in the center of the barrier to dramatically improve its durability, tear and hanging strength.

Modular certain panels are constructed with grommets across the top and bottom, and exterior grade Velcro seals along the vertical edges. Modular panels are sewn with an exterior grade thread.



### FEATURES:

- STC 26 Rating
- Excellent outdoor UV and weather resistance
- Available barrier colors: gray, tan, olive drab or green





Intelligent Acoustic Solutions

SPEC DATA SHEET # GWC\_EX-R



**APPLICATIONS:**

Typically used as a modular certain panels on long-term construction projects or permanent outdoor applications such as noise control around drilling equipment, enclosing HVAC equipment, dust collectors or similar machinery behind a manufacturing plant, where UV and abuse resistance as well as maximum durability, longevity and noise reduction is required. Also available with a two-inch thick quilted fiberglass absorber, or with a two-pound per sq. ft. reinforced barrier.

**PRODUCT DATA:**

**Description:** 1 lb-psf reinforced loaded vinyl noise barrier

**Nominal Thickness:** 0.090 inch

**Temperature Range:** -20Y to +180Y F

**Standard Panel Width:** 54" wide, lengths as required up to 16' high

**Weight:** 1.0 lb psf

**ACOUSTICAL PERFORMANCE:**

**Sound Transmission Loss:**

Product	OCTAVE BAND FREQUENCIES (HZ)						
	125	250	500	1K	2K	4K	NRC
GWC_EX-R	13	17	22	26	32	37	26

ASTM E-90 & E 413