



## SPEC DATA SHEET # SQ-115

4700 Clairton Blvd., Pittsburgh, PA 15236  
Tel: (412) 884-3000 • Fax: (412) 884-3300  
www.oeler.com • sales@oeler.com

# OI-400

## ACOUSTIC CEILING TILES

Oelex Acoustical Ceiling Tiles are offered as both a sound absorbing as well as a combination sound absorbing/sound blocking tile.

C-400 Ceiling Tiles have a black matte facing attached to a 1" or 2" thick rigid fiberglass board and have excellent sound absorption (NRC)

C-400B Ceiling Tiles take the standard C-400 tile and add a 1# foil backed mass-loaded vinyl to the backside of the tile for high sound absorption (NRC) and high sound blocking (STC) requirements.



### FEATURES:

- Black matte facing
- Custom sizes available
- Excellent acoustical values
- Offered with a vinyl noise barrier for high STC requirements





Intelligent Acoustic Solutions

SPEC DATA SHEET # OI-400



**FINISHES:**

Black matte facing

**SUBSTRATES:**

6-7# PCF rigid fiberglass core  
\*C-400B adds a vinyl noise barrier

**THICKNESS:**

1" or 2" thicknesses available

**EDGE DETAIL:**

Square

**WEIGHTS:**

C-400 Tile: .75lbs/ square foot (based on 1" thick)  
C-400B Tile: 1.75lbs/ square foot (based on 1-1/8" thick)

**SIZING:**

23-3/4"x 23-3/4" or 23-3/4"x 47-3/4" to fit into a standard 15/16" ceiling grid

**MOUNTING OPTIONS:**

Grid supplied by others

**SPECIFICATIONS:**

Specifications can be downloaded from our website  
[www.oeler.com/specs.html](http://www.oeler.com/specs.html) or call us at (412) 884-3000.