



SPEC DATA SHEET # OX-200

4700 Clairton Blvd., Pittsburgh, PA 15236
Tel: (412) 884-3000 • Fax: (412) 884-3300
www.oeler.com • sales@oeler.com

OX-200

ACOUSTIC WALL PANELS

Oelex Acoustical Wall Panels by Oeler Industries, Inc. are the solution for areas that require noise reduction and are available in a variety of models for various applications. The OX-200 Wall Panel is manufactured to the highest standards and is specifically designed as a standard absorber panel that offers an economical way to resolve reverberant noise problems. Application for the OX-200 panels includes schools, universities, offices, airports, churches, restaurants, and any area where excess reverberation is a problem.

The OX-200 provides the ultimate in performance with excellent NRC ratings. Available in four standard thicknesses: 1/2", 1", 1 1/2" and 2", with custom thickness available. OX-200 panels are constructed with a 6-7# PCF rigid fiberglass absorber core. The edges are chemically hardened and are available in four edge profiles. The OX-200 panels are available in standard or custom-sizes (up to a maximum of 5'x10') custom, designer or C.O.M fabric available.

Installation is simplistic using mechanical clips, adhesive or hook and loop. Consult with factory on the best-suited mounting for your specific application.



FEATURES:

- High-quality, economical, multi-purpose panels
- Excellent acoustical performance
- Class A fire rated
- Standard or designer or custom finishes





Intelligent Acoustic Solutions

SPEC DATA SHEET # OX-200



FINISHES:

Guilford of Maine FR701 Style 2100 is standard. Hundreds of approved decorator fabrics are also available from numerous manufacturers including, but not limited to: Guilford of Maine, Maharam, Carnegie and Knoll. Customers may also specify their own fabric, provided the material meets manufacturing requirements.

ACOUSTICAL DATA: NRC Rating

1/2":	.50 - .60
1":	.80 - .90
1 1/2":	.90 - 1.00
2":	1.05 - 1.15

SPECIFICATIONS:

Specifications can be downloaded from our website <https://www.oeler.com/resources/datasheets/> or call us at (412) 884-3000.

MOUNTING OPTIONS:



2-PART
MECHANICAL CLIPS



CLIP & VELCRO



IMPALING CLIP

ADDITIONAL DETAILS:

Available in a variety of edges as well as high-impact or reflective options.