



## SPEC DATA SHEET # OX-BBC-EXT

4700 Clairton Blvd., Pittsburgh, PA 15236  
Tel: (412) 884-3000 • Fax: (412) 884-3300  
www.oeler.com • sales@oeler.com

# OX-BBC-EXT

## BBC-EXT SOUND CURTAINS

OX-BBC-EXT 2" offers the benefits of both a noise barrier and a sound absorber composite in one product for outdoor applications. This barrier-backed product consists of an exterior grade, UV resistant heavy-duty faced quilted fiberglass absorber bonded to a one-pound per sq. ft. reinforced loaded vinyl barrier. The heavy-duty facing is a 10 oz per sq yd vinyl-coated-polyester (VCP) quilted to the sound absorber rather than the standard 4.5 oz. facing. Curtain panels are constructed with grommets across the top and bottom, exterior grade Velcro seals along the vertical edges, and are sewn with Gore Tenara exterior grade thread.

Modular curtain panels are constructed with grommets across the top and bottom, and exterior grade Velcro seals along the vertical edges. Modular panels are sewn with an exterior grade thread. The product is also available in roll form with edges bound or unbound.



### FEATURES:

- STC 32 Rating, NRC .85
- Available facing colors on quilt: gray, tan, black, off-white
- Available barrier colors: gray, tan, olive drab or blue
- Maximum durability and longevity outdoors





Intelligent Acoustic Solutions

SPEC DATA SHEET # OX-BBC-EXT



**ACOUSTICAL PERFORMANCE:**

**Sound Transmission Loss**

PRODUCT	OCTAVE BAND FREQUENCIES (Hz)						STC
	125	250	500	1000	2000	4000	
OX-BBC-EXT 2"	13	20	29	40	50	55	32

ATSM E-90 & E 413

**Sound Absorption Performance**

PRODUCT	OCTAVE BAND FREQUENCIES (Hz)						NRC
	125	250	500	1000	2000	4000	
OX-BBC-EXT 2"	.07	.27	.96	1.13	1.08	.99	.85

ASTM C 423

**SPECIFICATIONS:**

Specifications can be downloaded from our website <https://www.oeler.com/resources/datasheets/> or call us at (412) 884-3000.

**APPLICATIONS:**

Typically used as modular curtain panels on long-term construction projects or permanent outdoor applications such as enclosing HVAC equipment, dust collectors or similar machinery behind a manufacturing plant where UV and abuse resistance as well as maximum durability, longevity and noise reduction is required. Also available with a one-inch-thick quilted fiberglass absorber, or with a two-pound per sq. ft. reinforced barrier.

**PRODUCT DATA:**

**Description:** Vinyl coated polyester faced 2" quilted fiberglass/ 1 lb. psf reinforced loaded vinyl barrier

**Nominal Thickness:** 2.0 inches

**Temperature Range:** -20° to +180° F

**Standard Panel Width:** 54" wide, lengths as required up to 20' high

**Weight:** 1.45 lb. psf