



## OX-GWC-EXN

### Sound Curtains

Oelex GWC-EXN by Oeler Industries, Inc. is an economical noise barrier for outdoor applications. This barrier-wall product consist of a one-pound per sq. ft. non-reinforced loaded vinyl noise barrier. Modular curtain panels are constructed with grommets across the top and bottom, and exterior grade Velcro seals along the vertical edges. Modular panels are sewn with an exterior grade thread.

#### SPEC DATA SHEET # OX-GWC-EXN

4700 Clairton Blvd., Pittsburgh, PA 15236  
Tel: (412) 884-3000 • Fax: (412) 884-3300  
www.oeler.com • sales@oeler.com



#### FEATURES:

- STC 26 Rating
- Economical short-term solution
- Available barrier colors: black





Intelligent Acoustic Solutions

SPEC DATA SHEET # OX-GWC-EXN



**APPLICATIONS:**

Typically used as modular curtain panels on short-term construction projects or other applications such as noise control around drilling equipment, enclosing HVAC equipment, dust collectors or similar machinery behind a manufacturing plant. This is an economical solution where cost is an issue during your project. Also available with a two-inch thick quilted fiberglass absorber, or with a two-pound per sq. ft. reinforced barrier.

**PRODUCT DATA**

**Description:** 1 lb-psf non-reinforced loaded vinyl noise barrier

**Nominal Thickness:** 0.107 inch

**Standard Panel Width:** 54" wide, lengths as required up to 16' high

**Weight:** 1.0 lb psf

**ACOUSTICAL PERFORMANCE:**

**Sound Transmission Loss:**

**OCTAVE BAND FREQUENCIES (HZ)**

Product	125	250	500	1K	2K	4K	NRC
GWC-EX-N	13	17	22	26	32	37	26

**SPECIFICATIONS:**

Specifications can be downloaded from our website <https://www.oeler.com/resources/datasheets/> or call us at (412) 884-3000.

