



SPEC DATA SHEET # OX-SR-200

4700 Clairton Blvd., Pittsburgh, PA 15236
Tel: (412) 884-3000 • Fax: (412) 884-3300
www.oeler.com • sales@oeler.com

OX-SR-200 SOUND ABSORPTION BAFFLES

Oelex SR-200 Baffles by Oeler Industries, Inc. are an economic, efficient solution to sound reverberation issues. The OX-SR-200 baffle is comprised of a poly-vinyl chloride bag encompassing a sound absorptive fiberglass, with a reinforced edge binding sewn around the entire perimeter of each baffle to prevent hanging baffles or as longer banners; either is available in white, gray, or black.

Grommets are installed for suspending the baffles or banners from wire or cable ties.



FEATURES:

- NRC rating 11.0 per 4'x2' baffle
- Class A (or 1) per ASTM E84
- The white facing is light reflective
- Lightweight, easy to install





Intelligent Acoustic Solutions

SPEC DATA SHEET # OX-SR-200



APPLICATIONS:

Typically used in areas where you want to introduce soft, sound absorption materials into hard, reflective environments to reduce the reverberant noise energy in a room. This creates an improved acoustical environment with lower noise levels and clearer communication in such applications as wood working facilities, manufacturing plants, gymnasiums, sports arenas, environmental control booths, and music rooms.

PRODUCT DATA

Description: 1.6lb/ft³ fiberglass core inside a sewn PVC bag.

Standard Thickness: 1", 1 1/2", 2" **Standard**

Size: Baffles: 48" x 24"; Banners 48" x any length to 25 feet

Notes: Additional sizes, fiberglass core densities and thickness available.

ACOUSTICAL PERFORMANCE:

(Sabin's per 4'x2')

OCTAVE BAND FREQUENCIES (HZ)

Product	125	250	500	1K	2K	4K	NRC
OX-SR-200 baffle	1.74	6.13	10.39	11.63	6.32	4.48	11.0

Test method: ASTM C423-99a

SPECIFICATIONS:

Specifications can be downloaded from our website <https://www.oeler.com/resources/datasheets/> or call us at (412) 884-3000.

