



SPEC DATA SHEET # OXC-100

4700 Clairton Blvd., Pittsburgh, PA 15236
Tel: (412) 884-3000 • Fax: (412) 884-3300
www.oeler.com • sales@oeler.com

OXC-100

ACOUSTICAL CEILING TILES

Our acoustical ceiling tile products are designed for high-performance absorption in standard drop ceiling grids. The Oelex OXC-100 Series ceiling tiles by Oeler Industries, Inc. offer both excellent acoustic performance with customizable options to enhance visual aesthetics.

Oelex acoustic ceiling tiles can be produced with absorptive elements, or a combination of absorption and sound blocking barriers.

OXC-100 ceiling tiles have a 2-mil white pebble grain vinyl facing attached to a 1" or 2" thick rigid fiberglass board and have excellent sound absorption (NRC) ratings.

OXC-100B ceiling tiles take the standard OXC-100 tile and add a 1 lbs/SqFt foil backed vinyl noise barrier to the backside of the tile for high sound absorption (NRC) and high sound blocking (STC) requirements.



FEATURES:

- Standard size 2'x2' or 2'x4'
- Custom sizes available
- 1" or 2" thickness
- 2 mil white pebble grain finish
- Excellent acoustical values
- Offered with vinyl noise barrier for high STC requirements





Intelligent Acoustic Solutions

SPEC DATA SHEET # OXC-100



FINISH

2 mil white pebble grain vinyl

ACOUSTICAL

NRC Rating

1" Thick ----- .85

2" Thick ----- 1.15

OXC-100B Version ----- STC 26

SUBSTRATE

6-7# PCF rigid fiberglass core

*OXC-100B adds a vinyl noise barrier

EDGE DETAIL Square

WEIGHTS

OXC-100 Tile .6 lbs/SqFt

OXC-100B Tile 1.6 lbs/SqFt

MOUNTING OPTIONS

Grid supplied by others

SPECIFICATIONS:

Specifications can be downloaded from our website

<https://www.oeler.com/resources/datasheets/>

or call us at (412) 884-3000.