



SPEC DATA SHEET # OXC-400

4700 Clairton Blvd., Pittsburgh, PA 15236
Tel: (412) 884-3000 • Fax: (412) 884-3300
www.oeler.com • sales@oeler.com

OXC-400

ACOUSTIC CEILING TILES

Oelex Acoustical Ceiling Tiles are offered as both a sound absorbing as well as a combination sound absorbing/sound blocking tile.

OXC-400 Ceiling Tiles have a black matte facing attached to a 1" or 2" thick rigid fiberglass board and have excellent sound absorption (NRC) ratings.

OXC-400B Ceiling Tiles take the standard OXC-400 tile and add a 1# foil backed mass-loaded vinyl to the backside of the tile for high sound absorption (NRC) and high sound blocking (STC) requirements.



FEATURES:

- Black matte facing
- Custom sizes available
- Excellent acoustical values
- Offered with a vinyl noise barrier for high STC requirements





Intelligent Acoustic Solutions

SPEC DATA SHEET # OXC-400



FINISHES:

Black matte facing

SUBSTRATES:

6-7# PCF rigid fiberglass core

*OXC-400B adds a vinyl noise barrier

THICKNESS:

1" or 2" thicknesses available

EDGE DETAIL: Square

WEIGHTS:

OXC-400 Tile: .75lbs/ square foot (based on 1" thick)

OXC-400B Tile: 1.75lbs/ square foot (based on 1-1/8" thick)

SIZING:

23-3/4"x 23-3/4" or 23-3/4"x 47-3/4" to fit into a standard 15/16" ceiling grid

MOUNTING OPTIONS:

Grid supplied by others

SPECIFICATIONS:

Specifications can be downloaded from our website

<https://www.oeler.com/resources/datasheets/>

or call us at (412) 884-3000.