



SPEC DATA SHEET # OX-400

4700 Clairton Blvd., Pittsburgh, PA 15236
Tel: (412) 884-3000 • Fax: (412) 884-3300
www.oeler.com • sales@oeler.com

OX-400 HIGH ABUSE PANELS

Oelex Acoustical Wall Panels by Oeler Industries, Inc. are the solution for areas that require noise reduction and are available in a variety of models for various applications. The OX-400 Wall Panel is manufactured specifically as a high abuse absorber panel that offers both excellent absorption and high durability. Application for the OX-400 panels includes gymnasiums, schools, universities, prisons, recreation centers and any area where excess reverberation and abuse resistance is required.

OX-400 High-Abuse Wall Panels are constructed using a high impact 1/4 6" thick perforated co-polymer underlayment laminated over a 1" or 2" thick 6-7 PCF fiberglass absorber core. The panels are fully wrapped in standard, custom or C.O.M fabric. Panels are available in 1 1/4 6" and 2 1/4 6" thickness with sizes up to a maximum of 4' X 10'.

OX-400 panels are easily installed using mechanical clips or adhesive and impaling clips. Consult with factory on the best-suited mounting for your specific application.



FEATURES:

- High-quality, economical, multipurpose panels
- Excellent acoustical performance Class
- A fire rated
- Standard, designer or C.O.M. fabric





Intelligent Acoustic Solutions

SPEC DATA SHEET # OX-400



FINISHES:

Guilford of Maine FR701 Style 2100 is standard. Hundreds of approved decorator fabrics are also available from numerous manufacturers including, but not limited to: Guilford of Maine, Maraham, Carnegie and Knoll. Customers may also specify their own fabric, provided the material meets manufacturing requirements.

**ACOUSTICAL DATA:
NRC Rating**

1 1/16"	.80 - .90
2 1/16"	1.05 - 1.15

SPECIFICATIONS:

Specifications can be downloaded from our website www.oeler.com/specs.html or call us at (412) 884-3000.

MOUNTING OPTIONS:



2-PART
MECHANICAL CLIPS



CLIP & VELCRO



IMPALING CLIP

ADDITIONAL DETAILS:

Available in a variety of edges as well as high-impact or reflective options.