




WoodTrends STANDARD FOR WALLS

- CLASS A FIRE-RATED COMPOSITES AVAILABLE
- NRC VALUES AS HIGH AS .90
- MDF, CHIPBOARD, OR PLYWOOD SUBSTRATES
- FLUSH OR REVEAL EDGE DETAIL AVAILABLE
- STANDARD PLANK SIZES: 4.5", 7.5", 9.4", 11.4"X 95", 108", 119"
CUSTOM PLANK SIZES AVAILABLE



WoodTrends Standard for Walls features a genuine wood plank wall treatment with perforations or grooves able to achieve NRC values as high as .90. The system is built on an MDF or chipboard core and the veneer is finished with 2 coats of a UV-polyacrylate lacquer. This system can be installed by the attachment of nailclips onto furring strips. WoodTrends Standard for Walls is offered in two edge details; reveal edge and flush edge. Reveal Edge detail leaves a 10mm groove between planks, with wood strips provided to conceal nailclips. Flush Edge detail features edges that butt together, so no wood strip is needed. A 2mm bevel defines the seam between the planks. Available in 24 standard and 40 custom veneers.



MAKING STATEMENTS IN WOOD

STANDARD
FOR WALLS

WoodTrends Standard for Walls

SOUND ABSORPTION DATA Frequencies (Hz)							
Perforation % of openings	125	250	500	1000	2000	4000	NRC
7.2 % open	0.29	0.58	0.55	0.51	0.48	0.53	0.55
18% open	0.13	0.34	1.15	1.08	0.55	0.53	0.80
24% open	0.27	0.81	0.78	0.95	0.96	0.93	0.90

* Acoustics is determined based upon % of opening in face of wood. Consult factory for availability.

STANDARD SPECIFICATIONS

SECTION 09570 - WOOD WALL PANELS

PART 1 - GENERAL

1.1 Scope - The work consists of furnishing all material, labor and accessories necessary to install WoodTrends Acoustical Wood Systems specified herein.

1.2 Delivery and Storage - All material shall be delivered in their original unopened cartons and stored in an enclosed area providing protection from damage and exposure to the elements. Prior to installation, panels shall be acclimated for 72 hours at the temperature and humidity conditions during installation and occupancy.

PART 2 - MATERIAL

2.1 Material

2.2 WoodTrends Acoustical Wood Systems as manufactured by Sound Seal, P.O. Box 545, Agawam, MA 01001.
Phone: 1-800-569-1294 Fax: 413-789-4444

2.3 Panels shall be WoodTrends Standard for Walls and be 16mm thick MDF with blind veneer backer, standard planks of 4.5", 7.5", 9.4", 11.4" x 95", 108", 119".

2.4 WoodTrends Standard panels shall be available in first quality select veneer from standard selection of 24 species, plus 40 additional species available with special staining and lacquering to match architects samples.

2.5 WoodTrends Standard panels shall be constructed using fire rated components meeting or exceeding the requirements of the ATSM E-84 Class _____ (A,B,C) Flame Spread: (A) 25 or less, (B) 26 to 75, (C) 76 to 200 Smoke Developed: 450 or less.

2.6 WoodTrends Standard panels shall have a minimum NRC rating of _____ with perforation pattern # _____, and an open area of _____%.

2.7 WoodTrends Standard panels shall be installed by means of nail clip on furring attached to wall substrate, with maximum nail clip spacing of 24".


PART 3 EXECUTION

3.1 Installation

3.2 WoodTrends Standard panels shall be installed as shown on interior elevation drawings and indicated on room finish schedule.

3.3 WoodTrends Standard panel installation shall not begin until all wet work is completed and panels have been allowed to acclimate for 72 hours. The installation contractor shall have at least 5 years of successful experience in this class of work. All WoodTrends Standard panels shall be properly installed and free from dirt, dust, grease, oils and fingerprints by wiping clean the surface with furniture polish.

Mounting Detail



REVEAL EDGE

- Uses real wood strip to hide nail clip
- All four edges finished
- 10 mm groove between planks
- Standard planks 4.5", 7.5", 9.4", 11.4" x 95", 108", 119"
- Custom sizes available



FLUSH EDGE

- No wood strip between planks required
- No need for finished edges
- 2 mm bevel defines seam between planks
- Standard planks 4.5", 7.5", 9.4", 11.4" x 95", 108", 119"
- Custom sizes available

Typical Veneer Selection

Afzelia	Conga Walnut
African Oak	Elm
American Oak	European Oak
Anigre	Koto
Ash	Khaya Mahogany
Beech Steamed	Maple
Beech Unsteamed	Oregon Pine
Birds-Eye Maple	Padouk
Black Walnut	Pear
Carolina Pine	Rosewood
Cedar	Sapeli Mahogany
Cherry	Teak

Other veneers available upon request.

For more information on WoodTrends products, please call us at 1-800-569-1294, or visit us online at: www.wood-trends.com.



50 H.P. Almgren Drive
Agawam, MA 01001

Phone: (413) 789-1770
Toll Free: 1-800-569-1294

Fax: (413) 789-4444
email: woodtrends@soundseal.com
www.wood-trends.com