

PRODUCT SHEET & SPECIFICATIONS

n.FORM[®]

CEILING PLATE SPEAKERS (STANDARD/INLINE)

MODELS LG035-G655 / LG035-G654 / LG035-G656-INLINE



FUNCTION

For spot treatments or when ceiling or site conditions (such as a gypsum ceiling) prevent the use of in-plenum speakers, direct fired speakers may be necessary.

The direct fired speakers have decorative speaker grills that blend seamlessly into your designs. The flush mounted speaker gently introduces the sound directly into the environment below. The inline speaker option also provides an additional volume control with an attenuator conveniently located next to the connectors. 0 to -12 dB adjustments can be made with a flathead screwdriver.

Speakers used in the n.FORM[®] system are configured with integrated RJ45 connections for plug and play and ease of installation. The speakers feature an aluminum housing, 5-inch diameter with wide dispersion, and weigh approximately four pounds each.

There are two speaker models available (6" & 4") to accommodate various plenum depths. Changes to speaker settings can be made either at the OP by channel or at a wall location via hand held remote or through the system's user interface on-site, off-site or around the world.

* UNITS ARE UL LISTED FOR USE IN AIR HANDLING SPACES

SPEAKER ENCLOSURE

- + Aluminum Housing
- + Grill Cover: Metal screen, white with perforated grill
- + Lightweight Mounting Chain
- + Two speaker models available – 6" & 4"

SPEAKER MODEL DIMENSIONS

LG035-G655	LG035-G654	LG035-G656-INLINE
H: 6"	H: 4"	H: 6"
D: 6"	D: 6"	D: 6"
W: 4lbs	W: 3lbs	W: 4lbs

LOUDSPEAKER

- + 5-inch diameter, wide dispersion
- + Power Rating – 10 watts RMS
- + Frequency Response – 50 – 12,000 Hz
- + Impedance – 32 Ohms
- + Resonance – 80 Hz
- + Magnet Weight – 10 oz
- + Magnet Structure Weight – 26 oz
- + Cone – Formed Fiber
- + Cone Suspension – High Compliance Foam
- + Voice Coil – 1-inch diameter
- + Voice Coil Form – Anodized Aluminum

PRODUCT SHEET & SPECIFICATIONS

n.FORM® SPEAKERS

MODEL LG035-G655 / LG035-G654 / LG035-G656-
INLINE

PAGING INPUT

+ Via 3RU Rack Headend & OP

POWER REQUIREMENT

+ Powered by OP

OTHER SYSTEM REQUIREMENTS

+ 16 gauge, plenum rated, stranded, 2-conductor wire
(for power supply to OP)

WIRE REQUIREMENTS

- + All wire must be plenum rated and UL listed
- + Speakers use Cat 5e or equivalent, 4 twisted pair
and RJ45 connectors
- + Straight cable – Pin 1 to Pin 1, Pin 2 to Pin 2, etc