

PRODUCT SHEET & SPECIFICATIONS

n.FORM®

DECORATIVE PENDANT/INLINE SPEAKER

MODELS G890-W / G890-B INLINE: G890-INLINE-W / G890-INLINE-B

*W = white B = black



FUNCTION

n.FORM® was designed to provide superior performance in Mass Notification and Emergency Communication (MNEC) solutions. n.FORM delivers a clearer, more intelligible message and audio signal and offers greater control and flexibility - ultimately delivering a smarter and more secure system.

The Pendant Speaker offers a decorative, direct fired option when aesthetics is a concern. With more open environments and exposed ceilings becoming the norm, a decorative solution has been difficult to find.

The speaker is constructed of high quality plastic, delivers superior sound quality and is easy to install. The Pendant Speaker comes with a gem box for Cat5e connections at the deck location which minimizes cable exposure for the client.

*The inline speaker option also provides an additional volume control with a remote attenuator. 0 to -12dB adjustments can be made from the remote.

SPEAKER ENCLOSURE

- + Plastic Housing
 - G890-W: White Housing
 - G890-B: Black Housing
 - G890-INLINE-W: White Housing
 - G890-INLINE-B: Black Housing
- + Grill: Metal screen, white or black with perforated grill

SPEAKER COVERAGE

- + 100 sq. ft. (nominal 10' speaker separation)

LOUDSPEAKER

- + Power Rating – 10 watt continuous, 20 watt peak
- + Frequency Response – 90-18 kHz
- + SPL for Output: 90 dB
- + Impedance – 32 Ohms
- + Speaker Weight – 1.1 lbs
- + Overall Speaker Dimension – 5.3"

AGENCY LISTINGS

- + UL1480

PRODUCT SHEET & SPECIFICATIONS

n.FORM® DECORATIVE PENDANT/INLINE SPEAKER

MODELS G890-W / G890-B INLINE: G890-INLINE-W / G890-INLINE-B

PAGING INPUT

- + Via 3RU Rack Headend & OP

POWER REQUIREMENT

- + Powered by OP

WIRE REQUIREMENTS

- + All wire must be plenum rated and UL listed
- + Speakers use Cat 5e or equivalent, 4 twisted pair and RJ45 connectors
- + Straight cable – Pin 1 to Pin 1, Pin 2 to Pin 2, etc

OTHER SYSTEM REQUIREMENTS

- + 16 gauge, plenum rated, stranded, 2-conductor wire (for power supply to OP)